

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
11 January 2001 (11.01.2001)

PCT

(10) International Publication Number  
**WO 01/03359 A1**

(51) International Patent Classification<sup>7</sup>: **H04L 1/16**

(74) Agents: SLINGSBY, Philip, Roy et al.: Page White & Farrer, 54 Doughty Street, London WC1N 2LS (GB).

(21) International Application Number: **PCT/IB00/00962**

(22) International Filing Date: **3 July 2000 (03.07.2000)**

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:  
9915593.9 2 July 1999 (02.07.1999) **GB**

(71) Applicant (for all designated States except US): **NOKIA NETWORKS OY [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).**

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW). Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM). European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **METHOD AND SYSTEM FOR DATA RECEPTION ACKNOWLEDGEMENT**



(57) Abstract: A method for generating acknowledgement messages in a data transmission system having a receiver for receiving datagrams and being capable of determining which of a series of datagrams have been incorrectly received, the method comprising generating a plurality of a data units, each data unit comprising: a status bit indicative of the status of the data unit; and a plurality of spacing bits together forming a binary representation of a number at least partially indicative of the spacing between one incorrectly received datagram and a succeeding incorrectly received datagram.

WO 01/03359 A1